

Grade 80 Alloy Chain



Fehr Part#	Size (in)	Working Load Limit (lbs)	Ft/Full Drum	Ft/Half Drum	Wt (lbs)/Ft
18S250	9/32"	3,500	800	400	0.76
18S375	3/8"	7,100	400	200	1.52
18S500	1/2"	12,000	200	100	2.50
18S625	5/8"	18,100	150	75	3.10

Grade 80 Alloy Chain- a heat-treated steel chain with a high strength to weight ratio. The strength makes it safe for overhead lifting and lifting slings. It's also excellent for uses such as recovery, safety, and towing chains. Use only Grade 80 Alloy Chain and fittings for overhead lifting. Made to NACM Specifications.

Grade 80 Hammerlocks - Painted

Fehr Part #	Size (in)	Working Load Limit (lbs)	Wt (lbs)/Pail
HL281	1/4"	3,250	0.25
HL375	3/8"	7,100	0.75
HL500	1/2"	12,000	1.5
HL625	5/8"	18,100	2.5



Use only Grade 80 Alloy Chain and components for Overhead Lifting

Available in Stainless Steel through special order.

Weldless Rings



Size (in)	Oval - Forged Alloy Steel			Pear- Forged Carbon Steel		
	Fehr Part #	Working Load Limit (lbs)	Finish	Fehr Part #	Working Load Limit (lbs)	Finish
1/2"	ML500	4,100	Painted	PL500	2,900	Galvanized
5/8"	ML625	5,500	Painted	PL625	4,200	Galvanized
3/4"	ML750	8,600	Painted	PL750	6,000	Galvanized

Grade 80 Alloy Clevis Grab – Painted

Fehr Part #	Size (in)	WLL(lbs)	Wt (lbs)/Ea
G8CG250	1/4"	4,100	0.46
G8CG312	5/16"	5,100	0.75
G8CG375	3/8"	7,100	1.18
G8CG500	1/2"	12,000	2.50



Alloy Eye Hoist Hooks

Fehr Part #	WLL (lbs)	Wt (lbs)/Ea
HH1TA	1	1
HH1.5A	1.5	1
HH2TA	2	1
HH3TA	3	2
HH7TA	7	7.1



Alloy Deck Chains- Grade 80 chain



Fehr Part #	Size (in)	WLL (lbs)	Wt (lbs)/Ea
TAC500x003	1/2" x 3 ft.	12,000	6
TAC500x005	1/2" x 5 ft.	12,000	10

Tagged with Size, Grade, Reach and WLL

Also known as STAC chain