

# SAFETY DATA SHEET

NAME OF PRODUCT: SLIPIT® LW-Liquid

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: SLIPIT® LW-Liquid  
SYNONYMS:  
PRODUCT CODES: 32710, 50710, xx710

MANUFACTURER: Fehr Bros. Industries, Inc

ADDRESS: 895 Kings Highway  
Saugerties NY 12477

EMERGENCY PHONE: 800-255-3924  
CHEM-TELL PHONE: 800-255-3924  
OTHER CALLS: 845-246-9525  
FAX PHONE: 845-246-3330

CHEMICAL FAMILY: Petroleum hydrocarbons

PRODUCT USE: Lubricant

---

## SECTION 2: HAZARDS IDENTIFICATION

---

### POTENTIAL HEALTH EFFECTS

EYES: Yes - Irritation  
SKIN: Yes-Slight Irritation  
INGESTION: Yes  
INHALATION: Yes

ACUTE HEALTH HAZARDS: None Known

CHRONIC HEALTH HAZARDS: None Known

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known

### CARCINOGENICITY

OSHA: No                      ACGIH:                      NTP: No                      IARC: No

---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

Product name: SLIPIT® LW-Liquid

Hazardous Ingredients: No hazardous ingredients

Composition: The specific chemical identity and/ or exact percentage (concentration) of composition is proprietary and withheld.

### SECTION 3 NOTES:

Letter of Guarantee for entrance into USDA inspected sites may be found at [www.slipit.com](http://www.slipit.com). FDA accepted for use in applications with incidental food contact in accordance with CFR 178.3570. CFIA accepted for use in applications with incidental food contact.

---

## SECTION 4: FIRST AID MEASURES

---

EYES: Flush with plenty of water  
SKIN: Wash with soap and water  
INGESTION: Non-toxic – Induction of vomiting not required  
INHALATION: Remove to fresh air.

---

**SECTION 5: FIRE-FIGHTING MEASURES**

---

**FLAMMABLE LIMITS IN AIR, (% BY VOLUME):** UPPER: Not determined  
LOWER: Not determined

**FLASH POINT:** 395 F (COC)

**AUTOIGNITION TEMPERATURE:** 675 F (Estimated)

**NFPA HAZARD CLASSIFICATION**

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

**HMIS HAZARD CLASSIFICATION**

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

**EXTINGUISHING MEDIA:** Dry chemical powder, CO-2, Foam

**SPECIAL FIRE FIGHTING PROCEDURES:** Fire fighters should wear a NIOSH approved, pressure demand, self-contained breathing apparatus when fighting fires.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**ACCIDENTAL RELEASE MEASURES:** Contain spill – absorb with inert material. Do not use combustible materials such as sawdust.

---

**SECTION 7: HANDLING AND STORAGE**

---

**HANDLING AND STORAGE:** Do not transfer to unmarked containers. Store away from excessive heat, sparks, open flame or oxidizing materials. This product is not classified under DOT Regulations. NFPA Class 111B Storage.

**OTHER PRECAUTIONS:** No additional precautions or labels.

---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**ENGINEERING CONTROLS:**

**VENTILATION :** Local Exhaust: If needed to maintain workable concentration elow permissible exposure limit.

**RESPIRATORY PROTECTION:** Not required under conditions of normal use.

**EYE PROTECTION:** Not required under conditions of normal use

**SKIN PROTECTION:** Not required under conditions of normal use

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** None

**WORK HYGIENIC PRACTICES:** No unusual precautions

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

**APPEARANCE:** Light Tan Color

**ODOR:** Little or no odor

**PHYSICAL STATE:** Liquid

**pH AS SUPPLIED:** NA

**BOILING RANGE:** 570 F – 900 F Wide Range

**MELTING POINT:** 130 F

**FREEZING POINT:** ND

**VAPOR PRESSURE (mmHg):** below .0001 @ 20 C

**VAPOR DENSITY (AIR = 1):** N/A

**SPECIFIC GRAVITY (H2O = 1):** 0.945 @ 20 C

**EVAPORATION RATE:** Nil

**SOLUBILITY IN WATER:** Nil

**PERCENT SOLIDS BY WEIGHT:** 100%

**PERCENT VOLATILE:** 0%

**VOLATILE ORGANIC COMPOUNDS (VOC):** 0%

---

**SECTION 10: STABILITY AND REACTIVITY**

---

**STABILITY:** Stable  
**CONDITIONS TO AVOID (STABILITY):** Sparks – Open Flame  
**INCOMPATIBILITY (MATERIAL TO AVOID):** Strong oxidizers like chlorine and concentrated oxygen.  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Incomplete combustion will produce carbon monoxide and carbon dioxide.  
**HAZARDOUS POLYMERIZATION:** Will not occur  
**CONDITIONS TO AVOID (POLYMERIZATION):** NA

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**TOXICOLOGICAL INFORMATION:** LD50 (g/kg) – Les than 30

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**ECOLOGICAL INFORMATION:** No Data Available

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**WASTE DISPOSAL METHOD:** In accordance with federal, state and local regulations. Do not flush to drain/storm sewer. Contract authorized disposal service.  
**RCRA HAZARD CLASS:** Non-Hazardous Waste

---

**SECTION 14: TRANSPORT INFORMATION**

---

**U.S. DEPARTMENT OF TRANSPORTATION**  
**PROPER SHIPPING NAME:** Petroleum Lubricant  
**HAZARD CLASS:** NA (Non-Hazardous)  
**ID NUMBER:** NA  
**PACKING GROUP:** NA  
**LABEL STATEMENT:** NA – None Required

---

**SECTION 15: REGULATORY INFORMATION**

---

**U.S. FEDERAL REGULATIONS**  
**TSCA (TOXIC SUBSTANCE CONTROL ACT):** All Components Listed  
**311/312 HAZARD CATEGORIES:** Acute: No    Chronic: No    Fire: No    Reactivity: No

---

**SECTION 16: OTHER INFORMATION**

---

**OTHER INFORMATION:** SDS date: 2020